




The FON-870i delivers complete cordless convenience with uncompromising quality. With excellent audio even at the edges of its range, a superior full-duplex speakerphone, robust build quality and a large, bright color display, this is our best cordless phone ever. And with an impressive 18 hours of talk time on a single charge, this phone is a true business workhorse.

With support for up to 15 handsets per base and a range of 150 feet indoors, the FON-870i is also a snap to deploy. You can put a handset with its own extension number anywhere in your office without worrying about network drops.

Features

- Superior sound quality
- full-duplex speakerphone
- Up to 15 handsets per base
- Up to 10 simultaneous calls per base
- Long life: 18 hours talk and 200 hours standby time per charge
- Range up to 1000 feet (300m) outside, 150 feet (50m) inside
- Backlit color display
- Message waiting light
- 6 polyphonic ring tones
- 6 levels of ringer volume

- Adjustable key sounds
- Call log for incoming, outgoing and missed calls
- 170-entry phone book
- 2.5 mm headset jack
- Independent volume setting for speaker and handset
- Belt clip
- Redialing
- Optional auto-answer and hang up when the handset is lifted from or returned to the charging cradle



Sporting a sleek design and sturdy construction, the FON-870i is a high-performance wireless extension that's packed with features and easy to use.

- Crystal-clear sound quality
- Extensive battery life
- Large, bright 176 x 220 pixel color display

The FON-870i is supported for use in the US and Canada. For up-to-date availability information, visit www.fortivoice.com/availability.html.

ORDER INFORMATION

Product	SKU	Description
FortiFone FON-870i base station	FON-870i	FON-870i base station supports 200 FON-870i-H handsets, 10 concurrent calls and a range of 50m indoors and 300m outdoors.
FortiFone FON-870i handset	FON-870i-H	FON-870i-H handset, 176X220 color screen, 18+ hours of talk time, 200 hours of standby time, 3 softkeys.



Copyright© 2013 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, and FortiGuard®, are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance metrics contained herein were attained in internal lab tests under ideal conditions, and performance may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to the performance metrics herein. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any guarantees. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable. Certain Fortinet products are licensed under U.S. Patent No. 5,623,600.



